

<b>Technical parameters</b>							
Model(s):		Outdoor unit: MHA-V4W/D2N8-B Indoor unit: HB-A60/CGN8-B					
Air-to-water heat pump:		YES					
Water-to-water heat pump:		NO					
Brine-to-water heat pump:		NO					
Low-temperature heat pump:		NO					
Equipped with a supplementary heater:		NO					
Heat pump combination heater:		NO					
Declared climate condition:		AVERAGE					
Parameters are declared for medium-temperature application.							
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	4.4	kW	Seasonal space heating energy efficiency	$\eta_s$	129.5	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7°C	Pdh	3.89	kW	Tj = -7°C	COPd	2.17	-
Tj = 2°C	Pdh	2.38	kW	Tj = 2°C	COPd	3.30	-
Tj = 7°C	Pdh	2.94	kW	Tj = 7°C	COPd	4.41	-
Tj = 12°C	Pdh	1.32	kW	Tj = 12°C	COPd	5.66	-
Tj = bivalent temperature	Pdh	3.89	kW	Tj = bivalent temperature	COPd	2.17	-
Tj = operating limit	Pdh	3.42	kW	Tj = operating limit	COPd	1.91	-
For air-to-water heat pumps: Tj = -15°C	Pdh	-	kW	For air-to-water heat pumps: Tj = -15°C	COPd	-	-
Bivalent temperature	T <sub>biv</sub>	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	P <sub>cych</sub>	-	kW	Cycling interval efficiency	COP <sub>cyc</sub>	-	-
Degradation co-efficient (**)	Cdh	0.9	--	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>off</sub>	0.014	kW	Rated heat output (**)	P <sub>sup</sub>	0.98	kW
Standby mode	P <sub>sb</sub>	0.014	kW	Type of energy input	Electrical		
Thermostat-off mode	P <sub>to</sub>	0.024	kW				
Crankcase heater mode	P <sub>ck</sub>	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	2770	m <sup>3</sup> /h
Sound power level, indoors/outdoors	L <sub>WA</sub>	38/56	dB	For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h
Annual energy consumption	Q <sub>HE</sub>	2744	kWh				
For heat pump combination heater:							
Declared load profile	-			Water heating energy efficiency	$\eta_{wh}$	-	%
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).							
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							